

Scissor Lift

Used Scissor Lift Glendale - Scissor lifts are industrial equipment that relies on steel linked arms to lift vertically. Scissor lifts create an "X" support network to facilitate vertical lifting. Workers use a sizeable rectangle platform that is secured to the top of the lifting apparatus. To maintain operator safety, there are support railings at the top of the platform. This machine maintains a low profile that is ideal for hard surfaces such as concrete and other compact surfaces. This equipment relies on either a combustion engine or an electric motor to create the lift and transport the machine. The scissor lift operates on a vertical plane and if the operator needs to move the lift horizontally, they have to reposition the machine. The same lifting technology is used for the lifting components in regular scissor lift models as well as rough terrain models. The rough terrain is specially designed for traversing uneven ground. These machines rely on large all-terrain tires to allow rough terrain scissor lifts to traverse difficult locations while offering higher ground clearance. These scissor lifts feature 4WD to get through muddy and difficult terrain. Lower lifting heights are offered due to the higher center of gravity. Scissor lifts can seem intimidating if you have not used one before. While you may think this machine is susceptible to swaying in the wind or becoming unbalanced, understand that it has been designed to ensure total operator safety and that likely, you will not even feel the machine moving. Rigorous safety testing has to be completed prior to selling these machines. It is natural to feel unsure of these units until you can familiarize yourself with them. Safety precautions need to be maintained at all times. Depending on the application, there are a variety of electric scissor lift models to pick from. The unit you need will vastly depend on the kind of work you need to do. Key factors to consider include how high you will need to reach and the types of loads you will be moving. Extreme heights can be attained by different models depending on your specific application. Tinier models are often preferred for interior jobs such as factory, freight or warehousing situations. There is no reason to buy the biggest and best model on the market if you are not going to use the highest capacity. There are extra platforms and railings available to provide additional safety measures. These machines are designed to be reliable and safe. Of course, if these units did not undergo strict inspections and safety certification, they would not be for sale all over the world. These machines help us facilitate tasks that would otherwise not be possible. As these machines vertically elevate, the machine is transported into the correct location before lifting occurs. The operator needs to move the unit into the correct position before engaging the lift. There are a variety of safety features incorporated into the design. Safety is accomplished by following operational guidelines. Scissor lifts offer a secure basket workspace making many tasks much safer than trying to complete while dangling off of a ladder or scaffolding. The majority of scissor lifts utilize batteries that are internally mounted inside of the base of the lift to generate power. Electric scissor lifts need to be charged regularly; especially after prolonged work shifts. Numerous operators charge their units throughout the day or replace batteries every 12 hours. Scissor lifts are charged in a well-ventilated area, parked near an electrical outlet. When the machine is parked, the emergency shut-off switch becomes engaged to stop. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. Newer scissor lifts commonly have their battery charger on the right side of the unit. Older machines may feature a battery charger on the rear of the machine. The charger is plugged into the AC extension cord in an area that is well-ventilated and then the extension cord is plugged into an electrical outlet. It is essential that the electrical cord length on the battery charger is short to prevent being run over or damaged. There is a high possibility for extreme danger if excess extension cord length dropped out of the battery charger storage area during operation. Ideally, all of the lights on the charger should become illuminated after the scissor lift is plugged in. Once the unit is plugged in, the batteries automatically start to charge. The battery lights will switch to green once complete charging has occurred and the charger will shut off. Models that are older and rely on a meter will show zero volts after they are charged fully and then the charger will also turn off.

automatically. After the batteries are completely charged the scissor lift can complete another shift. It is common for warehouses and certain businesses to keep batteries charging around the clock to allow the scissor lift to operate 24 hours a day.